



Produs:

Tabla cutata H18 – Tabla cutata din table de otel prevopsit sau otel zincat.

Domeniu de utilizare:

- ✓ Acoperisuri si fatade
- ✓ Compartimentari
- ✓ Imprejmuiri

Caracteristici:

- ✓ Usor de instalat
- ✓ Set de scule uzual necesar instalarii
- ✓ Usor de manipulat si transportat

Standarde Europene:

EN 14782:2006 si EN 508-1

Comprtament la foc:

Reactie la foc: Class A1

Performanta la foc exterior: Class Broof (t1), Broof (t2), Broof (t3), Broof (t4)

Rezistenta mecanica:

1.2 kN la deschidere de 400 mm.

Accessorii:

Lungimi 1, 2 m

Latimi desfasurate: Cornier de margine 200mm, Coama dreapta 250 mm, Sort de streasina 156 mm

Materie prima	Otel zincat prevopsit	Otel Zincat
Marca de otel	S220GD+Z	
Greutate	2.9 kg/m ²	
Grosime	0.40 mm	
Protectie anticoroziva	225 g/m ²	
Strat de vopsea	Poliester 25 µm	Natur
Culori disponibile	3009, 3011, 8017, 7016, 6005	Natur / Zincat
Latime totala	1134 mm	915 mm
Latime utila	1084 mm	820 mm
Inaltime profil	18 mm	
Distanta de sipcuire	400 mm	
Panta minima	14°	
Garantie	10 ani	5 ani

